

## Model: 760MRL 230V Thermally enhanced optical smoke alarm

The 760MRL is a mains powered thermally enhanced optical smoke alarm with a rechargeable lithium battery back-up and a PUSH-FIT docking base system; designed to ensure quick and easy installation of base unit to the mains feed supply at installation stage (1st fix) and for quick and easy connection of alarm to base unit (2nd fix).

Thermally enhanced optical technology combines very latest in optical sensing with a thermal enhancement, providing fast reaction to both slow smouldering and fast flaming fires in a single alarm.



### Product features:

- 230V mains powered smoke alarm
- Rechargeable lithium battery back-up
- PUSH-FIT docking base (DS700 included)
- Thermally enhanced optical technology reduces nuisance alarms
- Test and alarm pause button
- Low battery warning
- Multi-alarm interlink (up to 12 smoke and heat units)
- LED operating indicators
- Alarm source indicator
- 5 year guarantee
- BS EN 14604: 2005

<b>Model number</b>	760MRL (1 x 660MRL + 1 x DS700 base)
<b>Description</b>	230V smoke with rechargeable battery bk-up
<b>Technology</b>	Thermally enhanced optical
<b>Sensitivity</b>	N/A
<b>Alarm sound level</b>	85db at 3 metres
<b>Battery type</b>	Rechargeable lithium
<b>Operation AC/DC</b>	AC
<b>Installation positions</b>	Ceiling
<b>Operating temperature</b>	5°C (40°F) to 38°C (100°F)
<b>Operating humidity</b>	10% to 85% relative
<b>Storage temperature</b>	5°C (40°F) to 38°C (100°F)
<b>Storage humidity</b>	10% to 85% relative
<b>Warranty</b>	5 years

<b>Dimensions - Alarm + Base</b>	140mm (D) x 53mm (H)
<b>Dimensions - Base</b>	140mm (D) x 33mm (H)
<b>Unit weight - Alarm</b>	249g
<b>Unit weight - Base</b>	91g
<b>Pack dimensions</b>	141mm (H) x 141mm (W) x 58mm (D)
<b>Pack weight</b>	TBC
<b>Master pack quantity</b>	10
<b>Master pack dimensions</b>	TBC
<b>Master pack weight</b>	TBC
<b>Pack barcode</b>	5022391065340
<b>Outer barcode</b>	15022391065347
<b>Approvals</b>	BS EN 14604: 2005